

Applicants : Yee Mau CHEN and Sum Pat POON
U.S. Serial No.: 10/776,971
Filed : February 11, 2004
Page : 2

Amendments to the claims:

Please cancel claims 1-13 without prejudice to Applicants' rights to pursue the canceled subject matter in a future application or applications, and add new claims 14-32.

1-13. (Canceled)

14. (New) A brewing filter apparatus for a coffee- or beverage- making machine, comprising a handle attached to a receiving or brewing container, a filter, an outlet nut fixed to the container and a foam maker attached to the outlet nut.

15. (New) The brewing filter apparatus of claim 14, wherein the handle, container or filter is made, formed or fabricated of stainless steel, plastic, such as heat resistant plastic a suitable metal.

16. (New) The brewing filter apparatus of claim 14, wherein the outlet nut comprises an opening for creating foam or froth.

17. (New) The brewing filter apparatus of claim 16, wherein the diameter of the opening is between 0.8mm to 2.0mm.

18. (New) The brewing filter apparatus of claim 14, wherein the foam maker is suitably positioned to permit one or more jets of brewed coffee or beverage to make contact with the bottom of the foam maker to produce foam.

19. (New) The brewing filter apparatus of claim 18, wherein the foam maker comprises an exit opening.

Applicants : Yee Mau CHEN and Sum Fat POON
U.S. Serial No.: 10/776,971
Filed : February 11, 2004
Page : 3

20. (New) The brewing filter apparatus of claim 19, wherein the opening on the foam maker is positioned away from the jets of brewed coffee or beverage.

21. (New) The brewing filter apparatus of claim 14, further comprising a detachable mesh.

22. (New) The brewing filter apparatus of claim 21, wherein the mesh is pivotally connected by a hinge.

23. (New) A device comprising the brewing filter apparatus of claim 14.

24. (New) A brewing filter apparatus for a coffee- or beverage-making machine, said apparatus being useful for preparing a brewed beverage having a froth or foam layer, the improvement comprising,

a handle attached to a receiving or brewing container, said handle and said container being adapted for measuring and receiving an appropriate amount of coffee grounds or brew-able substance, and said container being adapted for brewing coffee grounds or brew-able substance when the container is placed in said coffee- or beverage-making machine and for reducing the amount of water remaining in said brewing filter apparatus after the completion of the brewing process;

a filter remove-ably mounted in said container;

an outlet nut, one end of said outlet nut is attached to the bottom portion of said container;

a foam maker attached to the other end of said outlet nut;

Applicants : Yee Mau CHEN and Sum Fat POON
U.S. Serial No.: 10/776,971
Filed : February 11, 2004
Page : 4

a foam chamber formed by the inner walls of said outlet nut and said foam maker,

wherein said foam maker includes one or more exit opening to permit foam and brewed beverage to exit the foam chamber,

wherein said outlet nut comprises at least one opening for providing fluid communication between the container and the foam chamber, and for delivering one or more jet of brewed beverage to the foam chamber; and

said outlet nut and said foam maker is arranged such that foam is produced when one or more jet of brewed beverage makes contact with the bottom portion of said foam chamber.

25. The brewing filter apparatus of claim 24, wherein the diameter of the opening is between 0.8mm to 2.0mm.

26. (New) The brewing filter apparatus of claim 24, further comprising a detachable mesh.

27. (New) The brewing filter apparatus of claim 26, wherein the mesh is pivotally connected by a hinge.

28. (New) The brewing filter apparatus of claim 24, wherein the foam maker and the outlet nut are cast, molded, fabricated or formed as a single member.

29. (New) A brewing filter apparatus for a coffee or beverage device, comprising:

a handle attached to a receiving or brewing container;

a filter remove-ably mounted on the container;

Applicants : Yee Mau CHEN and Sum Fat POON
U.S. Serial No.: 10/776,971
Filed : February 11, 2004
Page : 5

an outlet nut, one end of the outlet nut is attached to the bottom portion of the container;

a foam maker attached to the other end of the outlet nut; and

a foam chamber form by the inner walls of the outlet nut and the foam maker, the foam maker includes one or more exit opening to permit foam and brewed beverage to exit the foam chamber,

wherein the outlet nut includes one or more opening for providing fluid communication between the container and the foam chamber, and for providing jet(s) of brewed beverage to the foam chamber, the diameter of the opening is between 0.8 to 2.0 mm,

wherein the exit opening on the foam maker is positioned away from the jet(s) of brewed beverage flowing into foam chamber, and foam is created when jet(s) of brewed beverage makes contact with the bottom portion of the foam chamber.

30. (New) The brewing filter apparatus of claim 29, further comprising a detachable mesh.

31. (New) The brewing filter apparatus of claim 30, wherein the mesh is pivotally connected by a hinge.

32. (New) The brewing filter apparatus of claim 29, wherein the foam maker and the outlet nut are cast, molded, fabricated or formed as a single member.